

1" - 64" DUCTILE IRON FLANGED FITTINGS

Material: Ductile iron per ASTM A536

Pressure: 250 PSI rating for 1" - 48" sizes and 150 PSI rating for 54" - 64"

Testing: In accordance with ANSI/AWWA C110/A21.10, UL and FM requirements

Laying Length: 2" - 48" sizes in accordance with ANSI/AWWA C110/A21.10 and ANSI B16.1 and 54" - 64" sizes in accordance

with ANSI/AWWA C153/A21.53 (fittings not listed in ANSI/AWWA have dimensions per Star design as noted in the catalog)

Weights: Are in pounds, unless noted otherwise and do not include accessories, cement lining and coatings

Drilling: In accordance with ANSI/AWWA C110/A21.10, ANSI/AWWA C153/A21.53 and ANSI B16.1 Class 125 Flanges

Cement Lining: In accordance with ANSI/AWWA C104/A21.4 — sizes 1"- 3" single thickness and sizes 4"- 64" double thickness

Coating: Asphaltic seal coat inside in accordance with ANSI/AWWA C104/A21.4 and prime coat outside

Approvals: 4" - 12" Underwriters Laboratories Listed and Factory Mutual approved for 300 PSI rating 2" and greater are UL/NSF-61

Dimensions: All dimensions are in inches unless noted otherwise

FLANGE 90 BEND DI

FLANGE 90 BASE BEND DI

FLG LONG RADIUS 90 BEND DI

FLG LONG RADIUS BASE 90 BEND DI

FLG SIDE OUTLET 90 BEND DI

FLANGE 45 BEND DI

FLANGE 22 1/2 BEND DI

FLANGE 11 1/4 BEND DI

FLANGE REDUCING 90 BEND DI

FLANGE TEE DI

FLANGE BASE TEE DI

FLANGE REDUCING RUN TEE DI

FLANGE BULLHEAD TEE DI

FLANGE CROSS DI

FLANGE CONCENTRIC REDUCER DI

FLANGE ECCENTRIC REDUCER DI

FLANGED TRUE WYE DI

FLANGE LATERAL DI

BLIND FLANGE

BLIND FLANGE W/2 TAP

FLANGE x FLARE 90 BEND DI

FLANGE X FLARE PIECE DI