

HYDRANT

3-way

(approved to UL 246, FM 1510, ANSI/AWWA C502 Standards) -

4-1/2" main valve opening three way (two hose nozzles and one pumper nozzle)

5-1/4" main valve opening three way (two hose nozzles and one pumper nozzle)

2-way

(approved to ANSI/AWWA C502 Standards) -

4-1/2" main valve opening two way (two hose nozzles)

5-1/4" main valve opening two way (two hose nozzles)

5-1/4" main valve opening two way (two pumper nozzles)

1-way

(approved to ANSI/AWWA C502 Standards)-

4-1/2" main valve opening one way (one pumper nozzle)

- Meets all applicable parts of ANSI/AWWA C502 Standard
- Post type dry barrel design
- Dry top design with O-ring sealed oil reservoir
- Traffic feature with stainless steel safety stem coupling
- Compression-type main valve closes with pressure for positive seal; it is made of rubber and is conveniently reversible providing a spare for long service life
- Operating nut available in wide variety of shapes and sizes-open left or right
- Field replaceable hose and pumper nozzles
- Hose and pumper nozzles have large radius, full flow openings for low friction loss
- Contoured shoe is designed for full flow
- Dual bronze drain valves provide effective barrel drainage
- 250 psig (1723 kPa) maximum working pressure, 500 psig (3447 kPa) static test pressure for 3-way hydrants;
- 200 psig (1379 kPa) maximum working pressure, 400 psig (2758 kPa) static test pressure for 2-way and 1-way hydrants

