

2" - 64" DUCTILE IRON MJCOMPACT FITTINGS

Material: Ductile Iron per ASTM A536

Pressure: 350 PSI rating for 3" - 24" sizes, 250 PSI rating for 30" - 48" sizes and 150 PSI rating for 54" - 60" sizes

Testing: In accordance with ANSI/AWWA C153/A21.53 and UL requirements

Laying Length: In accordance with ANSI/AWWA C153/A21.53 (fittings not listed in ANSI/AWWA have dimensions per Star

design as noted in the catalog)

Weights: Are in pounds, unless noted otherwise and do not include accessories, cement lining and coating

Flanges: Flanged ends on fittings match ANSI/AWW C115/A21.15 and ANSI B16.1 class 125 flanges

Cement Lining: In accordance with ANSI/AWWA C104/A21.4 — size 2" - 3" single thickness and sizes 4" - 64" double thickness

Coating: Asphaltic seal coat inside and out in accordance with ANSI/AWWA C104/A21.4

Gaskets: SBR in accordance with ANSI/AWWA C111/A21.11 (see pg. 17)

T-Bolts/Nuts: Low alloy steel in accordance with ANSI/AWWA C111/A21.11 (see pg. 16)

Approvals: 4" - 12" Underwriters Laboratories Listed 3" and greater are UL/NSF-61

C153 MJ 90 BEND

C153 MJ 45 BEND

C153 MJ 22 1/2 BEND

C153 MJ 11 1/4 BEND

C153 MJXPE 90 BEND

C153 MJXPE 45 BEND

C153 MJXPE11 1/4 BEND

C153 MJ TEE

C153 MJ X FLG TEE

C153 MJ TAPPED TEE

C153 MJ HYDRANT TEE

C153 MJ REDUCER

C153 MJ LEB REDUCER

C153 MJ SEB REDUCER

C153 MJ SHORT SLEEVE

C153 MJ LONG SLEEVE

C153 DUAL PURPOSE SLEEVE

C153 MJ CROSS

C153 MJ LATERAL

C153 MJXFLG ADAPTER

C153 MJ CAP

C153 MJ TAPPED CAP

C153 MJ PLUG

C153 MJ TAPPED PLUG