

## TRANSITION COUPLING

**CENTER BARREL:** Ductile Iron per ASTM A536 and AWWA C219.

**END GLANDS:** Ductile Iron per ASTM A536 and AWWA C219.

**GASKET:** SBR transition design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per AWWA C219. Suitable for mild acids, water, and salt media with a temperature range of -40° F to +150° F.

**BOLTS & NUTS:** Low Alloy Steel per ASTM A325, ASTM A563, and AWWA C219. (Stainless Steel also available)

**FINISH:** Epoxy.

**Sizes:** 2" – 48".



## LONG BARREL TRANSITION COUPLING

**CENTER BARREL:** Ductile Iron per ASTM A536 and AWWA C219.


**END GLANDS:** Ductile Iron per ASTM A536 and AWWA C219.

**GASKET:** SBR transition design from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per AWWA C219. Suitable for mild acids, water and salt media with a temperature range of -40° F to +150° F.

**BOLTS & NUTS:** Low Alloy Steel per ASTM A325, ASTM A563, and AWWA C219.

**FINISH:** Epoxy.

**Size:** 2" – 24"



## WIDE-RANGE COUPLING (Long Barrel Available)

**CENTER BARREL:** Ductile Iron per ASTM A536 and AWWA C219.

**END GLANDS:** Ductile Iron per ASTM A536 and AWWA C219.

**GASKET:** SBR transition design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per AWWA C219. Suitable for mild acids, water and salt media with a temperature range of -40° F to +150° F.

**BOLTS & NUTS:** Low Alloy Steel per ASTM A325, ASTM A563, and AWWA C219.

**FINISH:** Epoxy.

**Size:** 2" – 16"

*One range fits all pipe ODs IPS PVC to Rough Barrel AC*



## WIDE-RANGE(stainless) COUPLING

**CENTER BARREL:** Type 304 (18-8) Stainless Steel.

**END GLANDS:** Type 304 (18-8) Stainless Steel.

**GASKET:** SBR transition design produced from 100% new rubber to ensure performance under varying pressures with superior storage characteristics per ASTM D2000. Suitable for mild acids, water and salt media with a temperature range of -40° F to +150° F.

**BOLTS & NUTS:** Type 304 (18-8) Stainless Steel per ASTM A193 and A194.

**NOTE:** Hex nuts are furnished with fusion bonded coating to prevent seizing and galling.

*One range fits all pipe ODs IPS PVC to Rough Barrel AC*

